

AIRSTAGE

FUJITSU

# Cassette Range

Single Room Solutions



# Why Choose Fujitsu?

## Australia's Favourite Air®

Fujitsu General is a leading supplier of air conditioners in Australia, with a portfolio to suit both residential and commercial applications. We focus all of our research and manufacturing strengths into air conditioners which has resulted in our extensive range of world-class, energy efficient, market-leading air conditioners.

Fujitsu General strives to consistently provide high quality, reliable products accompanied by superior customer service. To be 'Australia's Favourite Air®' means to be the best air conditioning company to deal with in Australia, not just a leading air conditioning brand.

That's why we're proud to say we are 'Australia's Favourite Air®'.

## Fujitsu Channel Partner Network

Fujitsu have a comprehensive network of dealers right across Australia. This ensures that there is a local stockist in your area to assist you in purchasing a Fujitsu air conditioning system for your home.

## An Award-Winning Brand

Fujitsu understands that our customers are investing in our brand and trusting that we will provide their family with a comfortable living environment all year round.

Fujitsu is honoured to be voted Reader's Digest Most Trusted Brand in the Air Conditioning category from 2018-2022 and awarded highly commended in 2023 and 2024.



Fujitsu General has also won the ProductReview.com.au Best Appliance Brands award for 2023/2024.

## Peace of Mind

Fujitsu believe in the quality and reliability of every air conditioner we sell. This is why we're happy to provide a 5 year parts and labour warranty across the entire range.





✓  
Exceptional after sales service

✓  
Trusted brand

✓  
5 year manufacturer's warranty

### Sporting Chance

Fujitsu General Australia is extremely proud to be a major sponsor of the Sporting Chance Cancer Foundation. Established in 1996, Sporting Chance is a not-for-profit organisation that helps provide home support and care to children with cancer.



To date, Fujitsu General has donated more than \$10M to this worthy cause, with a percentage of sales from Fujitsu's air conditioning units going towards the funding of outreach programs and exploring better ways to treat and overcome cancer.

Sporting Chance initiatives allow families to spend more quality time at home together, while still having access to the appropriate care for their child.

### State of the Art Research and Development

Our state of the art research and development centre, located at our headquarters in Japan, is equipped with numerous testing facilities simulating a variety of air conditioning operating conditions. Our rigorous testing aims to meet Fujitsu's high standard of product quality and reliability.

### Exceptional After Sales Service

At Fujitsu, we pride ourselves on providing exceptional customer service. Fujitsu General Assist is our in-house customer care and technical support department which was implemented to deliver a high level of support and accessibility to our customers.

Fujitsu General Assist deploys Fujitsu-trained technicians in Sydney, Melbourne, Brisbane, Adelaide, and Perth and provides access to dedicated Service Agents in all other parts of Australia. These technicians are well equipped with the necessary tools and spare parts to enable them to resolve issues onsite, promptly. This offers customers a high first time fix rate and seamless experience.





# Cassette Range

**12** models  
from 2.5kW  
to 13.0kW  
Cooling capacity



## Why Choose Our Cassette Range?

Our Cassette range of air conditioners are suitable for both residential and commercial applications. Ceiling mounted, they are discreet and provide great airflow for ultimate comfort and control, all year round.

## Visually Discreet

The Fujitsu General range of Cassette air conditioning units are visually discreet, with a non-intrusive grille design that sits neatly under the ceiling.

## Even Temperature Distribution

Incorporating Fujitsu's latest fan design and technology, air can be distributed throughout the space in multiple directions, providing even temperature distribution and all-round comfort.

## Simple Comfort Control

Ideal comfort can be enabled via the easy-to-use controller. Super quiet mode means the indoor fan operates at low speed to produce less noise. Use program timers to turn your unit on and off at set times.

## 50° Celsius Operation

The Circular Flow Cassette range and the Compact Cassette AUTH24KVL model have a cooling operation range of up to 50°C ambient temperature and improved heating capacity in low outdoor temperatures.

## Energy Efficiency

Energy management features such as programmable weekly timers, a sleep timer<sup>1</sup> and economy mode offers an efficient cooling and heating solution. The Cassette range is ideal for larger open plan spaces, such as offices and retail outlets.

## Easy to Maintain

With a removable indoor unit intake grille<sup>2</sup>, the Cassette range can be kept clean and maintained easily, while louvres can be wiped down to remove any dust for a cleaner air flow.

## Demand Response Enabled

The Circular Flow Cassette and Compact Cassette range are compatible with the Air Conditioning Demand Response program. When your electricity supplier activates one of the three modes, the air conditioner switches over to the appropriate operation.

## Human Sensor Control<sup>3</sup>

An optional intelligent feature, available in the Circular Flow Cassette range, that detects the movement of people to deliver optimum efficiency and temperature control. When in operation, if the sensor detects no movement in a room after 20 minutes, the unit will automatically switch to energy-saving operation, modifying the temperature to minimise energy consumption. When movement is detected within the room, the unit reverts back to its previous setting.

<sup>1</sup>Weekly timer and sleep timer not applicable to the Compact Cassette.

<sup>2</sup>Not applicable to the Circular Flow Cassette.

<sup>3</sup>Optional part is only available for the Circular Flow Cassette with white grille.

# Compact Cassette

- ✓ 4 models from 2.5kW to 7.1kW cooling capacity
- ✓ High energy saving and quiet operation
- ✓ Compact grille design
- ✓ Precise temperature control, in 0.5 increments
- ✓ R32 refrigerant
- ✓ High efficiency design through 2-stage turbo fan for even air distribution
- ✓ High ceiling mode - can be installed up to a ceiling height of 3m<sup>1</sup>

## Indoor unit



AUTH09KVLA

2.5kW | 3.2kW  
cooling | heating

AUTH12KVLA

3.5kW | 4.0kW  
cooling | heating

AUTH18KVLA

5.0kW | 6.0kW  
cooling | heating

AUTH24KVLA

7.1kW | 8.0kW  
cooling | heating

## Outdoor units



AOTH09/12KBTA



AOTH18KBTA



AOTH24KBTB

## Standard controller



Standard Controller  
AR-REJ1E

## Available optional controllers



anywAIR<sup>®</sup>  
Technology Wi-Fi  
Adaptor II  
UTY-NXT-BOX<sup>2</sup>  
UTY-NXT-CAB<sup>2</sup>



LCD Touch Panel  
Controller  
UTY-RNRYT5



LCD Simple  
Controller  
with Operation  
mode  
UTY-RSRYT



LCD Simple  
Controller  
without Operation  
mode  
UTY-RHRYT

<sup>1</sup>For AUTH12/18/24KVLA only

<sup>2</sup>Both UTY-NXT BOX (adaptor) and UTY-NXT-CAB (PCB to adaptor cable) are required for installation. Must be installed by a licenced installer.

# Circular Flow Cassette

- ✓ 8 models from 7.1kW to 13.0kW cooling capacity
- ✓ Unique circular flow creates a consistent and even temperature via multi-directional 360° airflow
- ✓ Black grille option available to suit any decor
- ✓ R32 refrigerant
- ✓ Energy efficient features including Human Sensor Control<sup>3</sup>

## Indoor units



## Single phase

AUTH24KRTA

7.1kW cooling | 8.0kW heating

AUTH30KRTA

8.5kW cooling | 10.0kW heating

AUTH36KRTA

10.0kW cooling | 11.2kW heating

AUTH45KRTA

12.5kW cooling | 14.0kW heating

AUTH54KRTA

13.0kW cooling | 15.5kW heating

## Three phase

AUTH36KRTA-3PH

10.0kW cooling | 11.2kW heating

AUTH45KRTA-3PH

12.5kW cooling | 14.0kW heating

AUTH54KRTA-3PH

13.0kW cooling | 15.5kW heating

## Outdoor units



Single phase

AOTH24KBTA



AOTH30/36KBTA



AOTH45/54KBTA

Three phase

AOTH36KRTA

AOTH45/54KRTA


## Available optional controllers



anywAir<sup>®</sup>  
Technology Wi-Fi  
Adaptor II  
UTY-NXT-BOX<sup>2</sup>  
UTY-NXT-CAB<sup>2</sup>



Kagami  
Controller  
UTY-RVRY



LCD  
Touch Panel  
Controller  
UTY-RNRYTS



LCD Simple  
Controller  
with Operation  
mode  
UTY-RSRYT



LCD Simple  
Controller  
without Operation  
mode  
UTY-RHRYT



Infra-Red  
Controller<sup>1</sup>  
UTY-LBTYC

<sup>2</sup>Both UTY-NXT BOX (adaptor) and UTY-NXT-CAB (PCB to adaptor cable) are required for installation. Must be installed by a licenced installer.

<sup>3</sup>Black grille is not compatible with Human Sensor Control or IR receiver.

# Feature Checklist

|                                     |   | SET-AUTH09KVLA   | SET-AUTH12KVLA | SET-AUTH18KVLA | SET-AUTH24KVLA | SET-AUTH24KRTA             | SET-AUTH30KRTA | SET-AUTH36KRTA | SET-AUTH45KRTA | SET-AUTH54KRTA            | SET-AUTH36KRTA-3PH | SET-AUTH45KRTA-3PH | SET-AUTH54KRTA-3PH |
|-------------------------------------|---|------------------|----------------|----------------|----------------|----------------------------|----------------|----------------|----------------|---------------------------|--------------------|--------------------|--------------------|
|                                     |   | Compact Cassette |                |                |                | Circular Flow Single Phase |                |                |                | Circular Flow Three Phase |                    |                    |                    |
| <b>10C Heat Operation</b>           | The room temperature can be set to go no lower than 10C, ensuring that the room does not get too cold when not occupied   | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>All DC Components</b>            | Electricity loss is decreased and power consumption reduced   | ✓                | ✓              | ✓              | ✓              |                            |                |                |                |                           |                    |                    |                    |
| <b>Auto Changeover</b>              | Automatically switches between operating modes based on the temperature setting and room temperature  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Auto Restart</b>                 | The unit will automatically restart in the same operating mode after a temporary loss of power  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Automatic Airflow Adjustment</b> | The micro-processor automatically adjusts air flow to follow changes in room temperature  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Automatic Louvre</b>             | The position of the louvres is set automatically to match the operating mode. It is also possible to adjust the louvres using the remote control  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Blue Fin Heat Exchanger</b>      | Corrosion-resistance has been improved by blue fin treatment of the outdoor unit heat exchanger   | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Circular Flow Distribution</b>   | Creates a consistent and even temperature via multi-directional 360 airflow functionality   |                  |                |                |                | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Demand Response</b>              | Compatible with the Air Conditioning Demand Response program. When your electricity supplier activates one of the three modes, the air conditioner switches over to the appropriate operation |                  |                |                |                | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Economy Mode</b>                 | The temperature will adjust by 1°C to allow for a reduction in power drawn from the compressor  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Filter Sign</b>                  | Set the interval frequency to be reminded to clean the air filter on your unit  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>i-PAM</b>                        | i-PAM inverter technology enables high output and high efficiency performance   | ✓                | ✓              | ✓              | ✓              |                            |                |                |                |                           |                    |                    |                    |
| <b>On-Off Timer</b>                 | Can be set to operate once every 24 hours   | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Program Timer</b>                | Allows selection of one of four options. ON, OFF, ON-->OFF, or OFF-->ON   | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Removable Intake Grill</b>       | The indoor unit's intake grille can be removed for easy cleaning and maintenance  | ✓                | ✓              | ✓              | ✓              |                            |                |                |                |                           |                    |                    |                    |
| <b>Sleep Timer</b>                  | The micro-processor gradually changes the room temperature, allowing you to sleep comfortably at night  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Super Quiet Mode</b>             | The indoor unit's fan can operate at a low speed to produce quieter operation   | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>V-PAM</b>                        | v-PAM inverter technology increases the maximum output of the compressor significantly and enables high power and high efficiency   | ✓                | ✓              | ✓              | ✓              |                            |                |                |                |                           |                    |                    |                    |
| <b>Washable Panel</b>               | Dust that accumulates on the air conditioner can be easily cleaned with a damp cloth  | ✓                | ✓              | ✓              | ✓              | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |
| <b>Weekly Timer</b>                 | Different on-off timers can be set for up to 7 days   |                  |                |                |                | ✓                          | ✓              | ✓              | ✓              | ✓                         | ✓                  | ✓                  | ✓                  |



# Product Specifications

## Compact Cassette

|                                       |                                |            |                       | NEW MODEL             |                       |                       |           |
|---------------------------------------|--------------------------------|------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------|
| Set Code                              |                                |            | SET-AUTH09KVLA        | SET-AUTH12KVLA        | SET-AUTH18KVLA        | SET-AUTH24KVLA        |           |
| Model No.                             | Indoor unit                    |            | AUTH09KVLA            | AUTH12KVLA            | AUTH18KVLA            | AUTH24KVLA            |           |
|                                       | Outdoor unit                   |            | AOTH09KBTA            | AOTH12KBTA            | AOTH18KBTA            | AOTH24KBTB            |           |
| Power Source                          | V / Ph / Hz                    |            | 230 / 1 / 50          |                       |                       | 220 - 240 / 1 / 50    |           |
| Capacity                              | Cooling (Rated (Min - Max))    | kW         | 2.50 (0.9 - 3.6)      | 3.50 (0.9 - 4.1)      | 5.00 (0.9 - 5.9)      | 7.10 (1.5-7.8)        |           |
|                                       | Heating (Rated (Min - Max))    | kW         | 3.20 (0.9 - 4.5)      | 4.00 (0.9 - 5.1)      | 6.00 (0.9 - 7.1)      | 8.00 (1.4-8.4)        |           |
| Input Power                           | Cooling (Rated (Max))          | kW         | 0.56 (1.13)           | 0.90 (1.33)           | 1.45 (2.39)           | 2.16 (2.72)           |           |
|                                       | Heating (Rated (Max))          | kW         | 0.76 (1.68)           | 1.04 (1.88)           | 1.71 (2.78)           | 2.21 (2.71)           |           |
| EER                                   | Cooling                        | kW / kW    | 4.46                  | 3.89                  | 3.45                  | 3.29                  |           |
| COP                                   | Heating                        | kW / kW    | 4.21                  | 3.85                  | 3.51                  | 3.62                  |           |
| Star Rating                           | Cooling: Hot/Average/Cold      |            | 4 / 3.5 / 3.5         | 3.5 / 3 / 3           | 3 / 2.5 / 2.5         | 2.5 / 2.5 / 2.5       |           |
|                                       | Heating: Hot/Average/Cold      |            | 3.5 / 3 / 2.5         | 3 / 2.5 / 2           | 3 / 2 / 1.5           | 3 / 2.5 / 2           |           |
| TCSPF <sup>1</sup>                    | Residential (Hot/Average/Cold) | kW         | 5.804 / 5.126 / 5.179 | 5.206 / 4.74 / 4.862  | 4.666 / 4.325 / 4.474 | 4.401 / 4.187 / 4.365 |           |
| HSPF <sup>2</sup>                     | Residential (Hot/Average/Cold) | kW         | 5.064 / 4.575 / 4.108 | 4.822 / 4.268 / 3.714 | 4.574 / 3.954 / 3.376 | 4.58 / 4.044 / 3.533  |           |
| Running current                       | Cooling/Heating                |            | amps                  | 3.0 / 4.0             | 4.2 / 5.0             | 6.2 / 7.3             | 9.6 / 9.7 |
| Moisture Removal                      |                                |            | l/hr                  | 0.7                   | 1.2                   | 2.0                   | 3.4       |
| Sound Pressure Level                  | Indoor (Cooling)               | High/Quiet | dBA                   | 33 / 28               | 37 / 28               | 38 / 26               | 49 / 30   |
|                                       | Indoor (Heating)               | High/Quiet |                       | 34 / 27               | 37 / 28               | 43 / 30               | 50 / 33   |
|                                       | Outdoor (Cooling/Heating)      | High       |                       | 41 / 46               | 47 / 48               | 48 / 49               | 54 / 50   |
| Sound Power Level                     | Outdoor                        |            | High                  | 59                    | 61                    | 62                    | 69        |
| Air Circulation                       | Indoor (Cooling)               | High Fan   | l/sec                 | 150                   | 169                   | 189                   | 258       |
|                                       | Indoor (Heating)               | High Fan   |                       | 150                   | 169                   | 189                   | 286       |
| Dimensions H x W x D                  | Indoor                         |            | mm                    | 245 x 570 x 570       |                       |                       |           |
|                                       | Cassette grille                |            |                       | 49 x 620 x 620        |                       |                       |           |
|                                       | Outdoor                        |            |                       | 542 x 799 x 290       | 632 x 799 x 290       | 788 x 940 x 320       |           |
| Net Weight                            | Indoor                         |            | kg                    | 15.00                 | 15.00                 | 15.00                 | 16.00     |
|                                       | Cassette grille                |            |                       | 2.30                  | 2.30                  | 2.30                  | 2.30      |
|                                       | Outdoor                        |            |                       | 32.00                 | 32.00                 | 36.00                 | 53.00     |
| Connection Pipe Diameter (Liquid/Gas) |                                |            | mm                    | Ø6.35 / Ø9.52         |                       | Ø6.35 / Ø12.70        |           |
| Pipe Length (Max (Precharged))        |                                |            | m                     | 20 (15)               | 20 (15)               | 30 (20)               | 30 (30)   |
| Max Height Difference                 |                                |            | m                     | 15                    | 15                    | 20                    | 30        |
| Operation Range                       | Outdoor (Min - Max)            | Cooling    | °CDB                  | -10 to 46             | -10 to 46             | -10 to 46             | -10 to 50 |
|                                       |                                | Heating    |                       | -15 to 24             | -15 to 24             | -15 to 24             | -15 to 24 |
| Refrigerant                           | Type                           |            | R32                   | R32                   | R32                   | R32                   |           |
|                                       | Charge                         |            | g                     | 850                   | 850                   | 1,020                 | 1,500     |

<sup>1</sup> Total Cooling Seasonal Performance Factor

<sup>2</sup> Heating Seasonal Performance Factor

## Circular Flow Cassette

| SET- AUTH24KRTA       | SET- AUTH30KRTA       | SET- AUTH36KRTA       | SET- AUTH45KRTA       | SET- AUTH54KRTA       | SET- AUTH36KRTA-3PH   | SET- AUTH45KRTA-3PH   | SET- AUTH54KRTA-3PH   |
|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| AUTH24KRTA            | AUTH30KRTA            | AUTH36KRTA            | AUTH45KRTA            | AUTH54KRTA            | AUTH36KRTA            | AUTH45KRTA            | AUTH54KRTA            |
| AOTH24KBTA            | AOTH30KBTA            | AOTH36KBTA            | AOTH45KBTA            | AOTH54KBTA            | AOTH36KRTA            | AOTH45KRTA            | AOTH54KRTA            |
| 220 - 240 / 1 / 50    |                       |                       |                       | 380 - 415 / 3 / 50    |                       |                       |                       |
| 7.1 (1.8 - 8.1)       | 8.5 (2.8 - 10.3)      | 10.0 (2.8 - 11.4)     | 12.5 (4.0 - 14.0)     | 13.0 (4.5 - 15.0)     | 10.0 (2.8 - 11.4)     | 12.5 (4.0 - 14.0)     | 13.0 (4.5 - 15.0)     |
| 8.0 (2.0 - 9.1)       | 10.0 (2.7 - 11.3)     | 11.2 (2.7 - 14.0)     | 14.0 (4.2 - 16.5)     | 15.5 (4.7 - 18.0)     | 11.2 (2.7 - 14.0)     | 14.0 (4.2 - 16.5)     | 15.5 (4.7 - 18.0)     |
| 2.15 (2.73)           | 2.39 (4.07)           | 3.11 (4.11)           | 3.89 (4.9)            | 4.04 (5.19)           | 3.11 (4.11)           | 3.89 (4.9)            | 4.04 (5.19)           |
| 2.10 (2.59)           | 2.50 (4.39)           | 2.87 (4.35)           | 3.44 (4.9)            | 4.07 (5.23)           | 2.87 (4.35)           | 3.44 (4.9)            | 4.07 (5.23)           |
| 3.30                  | 3.56                  | 3.22                  | 3.21                  | 3.22                  | 3.22                  | 3.21                  | 3.22                  |
| 3.81                  | 4.00                  | 3.90                  | 4.07                  | 3.81                  | 3.90                  | 4.07                  | 3.81                  |
| 3 / 3 / 3             | 3.5 / 3 / 3.5         | 3 / 3 / 3             | 3 / 3 / 3             | 3 / 2.5 / 3           | 3 / 3 / 3             | 3 / 3 / 3             | 3 / 2.5 / 3           |
| 3.5 / 2.5 / 2         | 3.5 / 2.5 / 2         | 3.5 / 2.5 / 1.5       | 3.5 / 2.5 / 2         | 3 / 2 / 1.5           | 3.5 / 2.5 / 1.5       | 3.5 / 2.5 / 2         | 3 / 2 / 1.5           |
| 4.995 / 4.697 / 4.992 | 5.135 / 4.883 / 5.163 | 4.819 / 4.591 / 4.896 | 4.764 / 4.548 / 4.842 | 4.662 / 4.454 / 4.722 | 4.819 / 4.591 / 4.896 | 4.764 / 4.548 / 4.842 | 4.662 / 4.454 / 4.722 |
| 5.217 / 4.422 / 3.715 | 5.087 / 4.367 / 3.633 | 5.025 / 4.163 / 3.421 | 5.13 / 4.377 / 3.624  | 4.925 / 3.708 / 3.072 | 5.025 / 4.163 / 3.421 | 5.13 / 4.377 / 3.624  | 4.925 / 3.708 / 3.072 |
| 9.4 / 9.2             | 10.5 / 11.0           | 13.7 / 12.6           | 17.1 / 15.0           | 18.1 / 17.8           | 5.2 / 4.8             | 6.4 / 5.5             | 6.6 / 6.8             |
| 3.1                   | 2.6                   | 3.1                   | 4.8                   | 5.0                   | 3.1                   | 4.8                   | 5.0                   |
| 35 / 30               | 40 / 33               | 44 / 34               | 46 / 36               | 47 / 36               | 44 / 34               | 46 / 36               | 47 / 36               |
| 35 / 30               | 40 / 33               | 44 / 34               | 46 / 36               | 47 / 36               | 44 / 34               | 46 / 36               | 47 / 36               |
| 48 / 50               | 51 / 53               | 53 / 53               | 55 / 57               | 55 / 57               | 53 / 53               | 55 / 57               | 55 / 57               |
| 68                    | 69                    | 70                    | 71                    | 72                    | 70                    | 71                    | 72                    |
| 300                   | 417                   | 486                   | 542                   | 556                   | 486                   | 542                   | 556                   |
| 300                   | 417                   | 486                   | 542                   | 556                   | 486                   | 542                   | 556                   |
| 246 x 840 x 840       | 288 x 840 x 840       |                       |                       |                       |                       |                       |                       |
| 53 x 950 x 950        |                       |                       |                       |                       |                       |                       |                       |
| 716 x 820 x 315       | 788 x 940 x 320       |                       | 998 x 940 x 320       |                       | 788 x 940 x 320       | 998 x 940 x 320       |                       |
| 24.00                 | 26.00                 | 26.00                 | 29.00                 | 29.00                 | 26.00                 | 29.00                 | 29.00                 |
| 6.00                  | 6.00                  | 6.00                  | 6.00                  | 6.00                  | 6.00                  | 6.00                  | 6.00                  |
| 42.00                 | 52.00                 | 52.00                 | 67.00                 | 67.00                 | 53.00                 | 67.00                 | 67.00                 |
| Ø6.35 / Ø12.7         | Ø9.52 / Ø15.88        |                       |                       |                       |                       |                       |                       |
| 30 (20)               | 50 (30)               | 50 (30)               | 50 (30)               | 50 (30)               | 50 (30)               | 50 (30)               | 50 (30)               |
| 25                    | 30                    | 30                    | 30                    | 30                    | 30                    | 30                    | 30                    |
| -10 to 50             | -10 to 50             | -10 to 50             | -10 to 50             | -10 to 50             | -10 to 50             | -10 to 50             | -10 to 50             |
| -15 to 24             | -15 to 24             | -15 to 24             | -15 to 24             | -15 to 24             | -15 to 24             | -15 to 24             | -15 to 24             |
| R32                   | R32                   | R32                   | R32                   | R32                   | R32                   | R32                   | R32                   |
| 1250                  | 1900                  | 1900                  | 2700                  | 2700                  | 1900                  | 2700                  | 2700                  |

AUSTRALIA'S FAVOURITE AIR®

| FUJITSU

FUJITSU GENERAL AUSTRALIA  
A SUBSIDIARY OF FUJITSU GENERAL LIMITED

**[fujitsugeneral.com.au](http://fujitsugeneral.com.au)**  
**1300 882 201**  
**[contact@fujitsugeneral.com.au](mailto:contact@fujitsugeneral.com.au)**

Fujitsu General accepts no liability for incorrect data.  
Please ensure you have confirmed installation  
requirements and pipe sizes prior to install.

FGACASSETTE06/24

# AIRSTAGE